



MARVINACUSTICA

Less noise, better life.

Melange



WM / 126



WM / 132



WM / 129



WM / 133



WM / 106



WM / 127



WM / 138



WM / 142



WM / 130



WM / 128



WM / 135



WM / 134



WM / 111



WM / 104



WM / 131



WM / 108

Melange



WM / 105



WM / 124



WM / 125



WM / 139



WM / 122



WM / 140



WM / 143



WM / 141



WM / 102



WM / 112



WM / 114



WM / 101



WM / 137



WM / 136



WM / 103



WM / 120

Tinta Unita



WO / 02



WO / 06



WO / 01



WO / 04



WO / 03



WO / 05



WO / 08



WO / 11



WO / 10



WO / 07



WO / 12



WO / 09

**Composizione:**

100% Pura Lana Vergine

Resistenza all'abrasione:

>50000 cicli Martindale

Resistenza alla luce:

(EN ISO 105-B02)5

Resistenza allo sfregamento (EN ISO 105-X12):

Umido: 4/5 Secco: 5

Infiammabilità:

1 IM UNI 9175
EN 1021-1:2006
EN 1021-2:2006
TB 117:2013

Assorbimento acustico:

UNI EN ISO 354:2003

Caratteristiche del colore :

Leggere differenze di colore fra una fornitura e l'altra sono da considerarsi normali.

**Composition:**

100% Pure New Wool

Abrasion Resistance:

>50000 Martindale cycles

Light Fastness:

(EN ISO 105-B02)5

Fastness to Rubbing (EN ISO 105-X12):

Wet: 4/5 Dry: 5

Flammability:

1 IM UNI 9175
EN 1021-1:2006
EN 1021-2:2006
TB 117:2013

Acoustic Absorption:

UNI EN ISO 354:2003

Colour Characteristics:

Slight color difference between one lot and another have to be considered within commercial tolerance.

